PAGE: 1 PRINT DATE: 10/19/81

SHUTTLE CRITICAL ITEMS LIST - ORBITER NUMBER: 06-3D-050Z-X

SUBSYSTEM NAME: ATCS - RADIATORS AND FLOW CONTROL

REVISION: 10/19/88

CLASSIFICATION

NAME

PART NUMBER

LRU

FLOW CONTROL ASSY, RADIATOR 224-00050 FLOW CONTROL ASSY, RADIATOR MC203-0002-0050 LRU

QUANTITY OF LIKE ITEMS: 2 TWO, ONE PER LOOP

DESCRIPTION/FUNCTION: VALVE, RADIATOR FLOW CONTROL.

CONTROLS FREON COOLANT TEMPERATURE FROM THE RADIATOR PANEL ASSEMBLY. CONTROL IS ACCOMPLISHED BY MIXING HOT FREON WITH COLD RADIATOR FREON,

PAGE: 6	PRINT DATE: 10/19/8
SHUTTLE CRITICAL ITEMS LIST - ORBITER NUMBER: 06-30-0502-04	
SUBSYSTEM: ATCS - RADIATORS AND FLOW CONTROL	10/19/88
	CRITICALITY OF THIS PAILURE MODE: 2
FAILURE MODE: FAILS IN BYPASS POSITION, MECHANICAL JAMMING	
MISSION PHASE: OO ON-ORBIT	
VEHICLE/PAYLOAD/KIT EFFECTIVITY: 102 COLUMB	I.A.
: 103 DISCOV	
CAUSE: MECHANICAL SHOCK, CONTAMINATION, VIBRATION, CORROSION JAMMING.	N, PHYSICAL BINDING/
CRITICALITY 1/1 DURING ANY MISSION PHASE OR ABORT? M	
REDUNDANCY SCREEN A) M/A B) M/A C) M/A	
PASS/FAIL RATIONALE:	
B)	
c)	
	·
- FAILURE REFECTS -	
(A) SUBSYSTEM: POSSIBLE LOSS OF FREON FLOW IN ONE RADIATOR PANEL LOOP FOR VEHICLE COOLING.	

- (B) INTERFACING SUBSYSTEM(8): SAME AS A.

(C) MISSION: POSSIBLE LOSS OF MISSION DUE TO THE LOSS RADIATOR COOLING TO SUPPORT PAYLOAD OPERATIONS, A CRITICALITY 2/2 EFFECT.

SHUTTLE CRITICAL ITEMS LIST - ORBITER NUMBER: 06-3D-0502-04

(D) CREW, VEHICLE, AND ELEMENT(S): NO EFFECT.

RATIONALE FOR CRITICALITY:
FUNCTIONAL CRITICALITY EFFECT - ANY TWO ADDITIONAL FAILURES (OTHER
FREON COOLANT LOOP, HI-LOAD EVAPORATOR, AND AMMONIA BOILER SYSTEM) WILL
CAUSE LOSS OF VEHICLE COOLING CAPABILITY AND MAY RESULT IN LOSS OF
CREW/VEHICLE, A CRITICALITY 1R3 (PPP) EFFECT.

- DISPOSITION RATIONALE -

(A) DESIGN:

THE RADIATOR FLOW CONTROL VALVE DESIGN CONSISTS OF A DOUBLE POPPET TYPE VALVE HEAD, EACH HEAD HAVING A TEFLON SEALING RING WHICH SEALS AGAINST A CHAMFER SEAT WITHIN THE VALVE BODY. MATERIAL IS STAINLESS STEEL, WHICH IS COMPATIBLE WITH FREON 21. THE FLOW CONTROL ASSEMBLY IS MOUNTED ON VIBRATION ISOLATORS. THERE IS A 65 MICRON FILTER IN THE FLOW CONTROL ASSEMBLY.

(B) TEST:

QUALIFICATION TEST - FLOW CONTROL ASSEMBLY IS QUALIFIED FOR A 100 MISSION LIFE. VIBRATION TESTED AR 0.1 G2/HZ FOR 48 MIN/AXIS AND SHOCK TESTED AT +/- 20 G/AXIS.

ACCEPTANCE TEST - VALVE FUNCTIONAL TEST IS PERFORMED DURING ATP. AVT IS DONE AT COMPONENT LEVEL AND AT A HIGHER ASSEMBLY LEVEL (FLOW CONTROL ASSEMBLY).

OMRSD - RADIATOR FLOW CONTROLLER CHECKOUT (MANUAL AND AUTO) EVERY FIVE FLIGHTS. RADIATOR FLOW CONTROL VALVE OPERATION VERIFIED PRIOR TO EACH FLIGHT. FREON CHEMICAL ANALYSIS PER SE-S-0073 DURING SERVICING. FREON IS SERVICED THROUGH A FINAL FILTER OF 25 MICRON SIZE.

(C) INSPECTION:

RECEIVING INSPECTION

RAW MATERIAL CERTIFICATIONS ARE VERIFIED BY INSPECTION. PART PROTECTION IS VERIFIED BY INSPECTION.

CONTAMINATION CONTROL

CONTAMINATION CONTROL PROCESSES, CONTAMINATION CONTROL PLAN AND CORROSION PROTECTION PROVISIONS ARE VERIFIED BY INSPECTION. FLUID SYSTEM IS VERIFIED BY INSPECTION TO BE FREE OF CONTAMINATION.

ASSEMBLY/INSTALLATION

MANUFACTURING, INSTALLATION AND ASSEMBLY ARE VERIFIED BY INSPECTION FOR CRITICAL DIMENSIONS.

PAGE: 8 FRINT DATE: 10/19/8

SHUTTLE CRITICAL ITEMS LIST - ORBITER NUMBER: 06-30-0502-04

CRITICAL PROCESSES WELDING IS VERIFIED BY INSPECTION.

NONDESTRUCTIVE EVALUATION X-RAY EXAMINATION OF FUSION WELDS IS VERIFIED BY INSPECTION.

TESTING

VIBRATION, FLOW RATE AND PRESSURE DROP REQUIREMENTS ARE VERIFIED BY INSPECTION DURING ATP.

HANDLING/PACKAGING
HANDLING AND STORAGE ENVIRONMENTS ARE VERIFIED BY INSPECTION.

- (D) FAILURE HISTORY: NO FAILURE HISTORY.
- (E) OPERATIONAL USE:
 ON-BOARD ALARM, EVAPORATOR OUT TEMPERATURE, WILL INDICATE HARDWARE
 PAILURE. FAILURE WILL CAUSE AN EARLY END OF MISSION. FREON PUMP WILL
 BE TURNED OFF AND A POWERDOWN PERFORMED. FREON PUMP WILL BE
 REACTIVATED FOR ENTRY.

88/11/ ت

- APPROVALS -

RELIABILITY ENGINEERING: D. R. RISING DER

DESIGN ENGINEERING : O. TRAN ONT

QUALITY ENGINEERING : W. J. SMITH

NASA RELIABILITY NASA DESIGN

NASA QUALITY ASSURANCE :